



NDS[®]

We put water in its place

Chambers

Stronger & Easier to Maintain

**NDS[®] StormChamber[®]
is the most
cost effective
chamber solution**

Superior strength

Fast, easy installation

Simple maintenance

100+ year lifespan

Easy to specify


STORMCHAMBER[®]

ndspro.com

MADE IN
USA


The Preferred Underground Stormwater Solution



Thermo-formed High Density Weight Polyethylene HMWPE material won't crack.

- Meets H-20 standards
- Up to 16' cover when deep installs are required for the 34". Up to 12' for the 44"
- Stack in 2 or 3 layers for high storage capacity in a small footprint


STRENGTH & FLEXIBILITY



FAST INSTALLATION

Save time, money, and avoid extra excavation. Ideal for roadways, parking lots and fields.

- Built in end walls
- No header pipe manifold system required
- Flexible design
- Lowest installed cost



SIMPLE MAINTENANCE

Less time, less money and more forgiving.

- Differentiated and centralized sediment control through our propriety SedimenTrap™
- SedimenTrap™ gathers sediments and other pollutants in one place for quick, easy and inexpensive removal by vacuum truck



DURABILITY

Longest life expectancy on the market.

- Withstands the most extreme environments
- Material bends instead of breaks giving it a brittleness temperature of -107°F vs. industry average of -2°F
- 100 Year Life Expectancy




STACK


Allows for deeper installation and a smaller footprint

- 34" Chambers: Capable of 3-layer stacking
- 44" Chambers: Contact NDS DesignWorx for any projects that may need stacking
- We offer expert site-specific design guidance based on 20 years of successful completion of projects

NDS® StormChamber® Plan View (Configuration Example)



NDS® StormChamber® Elevated View



See How StormChambers Stack Up

	StormChamber	Competition
Header Pipe Mainfold In Flow/Out Flow	Not Required	Required
AASHTO H-20/H-193 Wheel Loaded Rating	Exceeds Standard	Meets Standard
End Caps to Purchase and Install	Not Required	Required
Maximum Height of Fill	up to 16' (4877 mm)	8' (2440mm)
Clean-out Inspection	In Minutes	Slow
Multilayer Installations	Up to 3 Layers	Single Layer

NDS® StormChamber®

Stock Code	Code	Short Description	Length	Width	Height	Weight	Per Pallet
SC-3475W-S	10SC	75CUFT START CHAMBER100X60X34	100"	60"	34"	90 Lbs	40
SC-3475W-E	10SC	75CUFT END CHAMBER100X60X34	100"	60"	34"	90 Lbs	40
SC-3475W-M	10SC	75CUFT MIDDLE CHAMBER100X60X34	100"	60"	34"	90 Lbs	40
SC-3475W-C	10SC	75CUFT CLOSED CHAMBER100X60X34	100"	60"	34"	90 Lbs	40
SC-3475-S	10SC	75CUFT START CHAMBER102X60X34	102"	60"	34"	100 Lbs	30
SC-3475-E	10SC	75CUFT END CHAMBER102X60X34	102"	60"	34"	100 Lbs	30
SC-3475-M	10SC	75CUFT MIDDLE CHAMBER102X60X34	102"	60"	34"	100 Lbs	30
SC-3475-C	10SC	75CUFT CLOSE CHAMBER102X60X34	102"	60"	34"	100 Lbs	30
SC-44105-S	10SC	105CUFT START CHAMBER90X78X44	90"	78"	44"	120 Lbs	20
SC-44105-E	10SC	105CUFT END CHAMBER90X78X44	90"	78"	44"	120 Lbs	20
SC-44105-M	10SC	105CUFT MID CHAMBER90X78X44	90"	78"	44"	120 Lbs	20
SC-44105-C	10SC	105CUFT CLOSE CHAMBER90X78X44	90"	78"	44"	120 Lbs	20
SC-ST	10SC	SEDIMENT TRAP	47" OD	-	2'	30 Lbs	4
SC-NWFF-500	10SC	FILTER FABRIC NON-WOVEN LIGHT	360'	12.5'	1.5' OD roll	220 Lbs	3
SC-WFF-75	10SC	STABILIZATION FABRIC WOVEN MEDIUM	75'	7.5'	0.75' OD roll	75 Lbs	16
SC-CF-E	10SC	CINTOFLEX NETTING	330'	6.5'	0.75' OD roll	7 Lbs	12
SC-FL-8	10SC	8" FRAME AND LID	10" OD	-	3"	20 Lbs	-
SC-3020P	10SC	30" X 20" HDPE PIPE	36" OD	-	20"	45 Lbs	4

We're Here to Help



DesignWorx™ by NDS®: NDS civil engineers and expert technicians are available to help make your project a success. We can evaluate and help you with the preparation of submittal drawings and specs to align with best stormwater practices. **(888) 825-4716** | ndspro.com/submitsyourdesign

Onsite support: Our customer support team will provide free on-site installation assistance, as needed.



Download our Mobile App – Search for NDS Drainage

Take the powerful resources of the NDS site with you on the go!
Access our product catalog, online calculators and planning tools.



Visit ndspro.com for:



Videos



Tools/
Calculators



Downloads



Case
Studies



Design
Worx



Request
a Quote

NDS Customer Service

8800 W. Hurley Ave, Visalia, CA 93291

Phone: 800.726.1994 (option 3)