

## Simple and Easy to Install — No Bolts, Washers, or Nuts Required

NDS rigid saddles have a unique patented wedge design for easy installation anywhere along the pipeline to add a branch connection in irrigation, agricultural, and mining applications. NDS Flo-Tap™ saddles are used in both hot tapping and wet tapping applications to tap into a water supply line without needing to shut off the water. NDS Clamp-It™ saddles are used to quickly add a sprinkler or riser to an existing pipeline and have proven success in copper and gold mines for heap leach mining.

Our rigid saddles are engineered for high-pressure and leak-free performance. NDS products are the contractors' preferred choice for pipe connections.



### Flo-Tap Saddle

- Grips securely onto pipe to add a branch off main line to make additional pipe connections
- Unique wedge design requires less installation space
- Features a 4-tip sawtooth cutter to capture debris and prevent it from entering the water supply



### Clamp-It Saddle

- Easy to install—simply bore hole in pipe, clamp saddle over hole, and tap wedge into place to secure
- Bolt-free wedge design saves time during installation
- Made of corrosion-proof material



**LEARN MORE  
ABOUT SADDLES**

NDS-ss-all-rigid-saddles-clamp-it-flo-tap-hot-wet-en.pdf

## Flo-Tap™ Rigid Hot/Wet Tap PVC Saddle for PVC Pipe

Pipe Pressure Rated @ 200 PSI @ 72°F | NSF/ANSI 61 +372 | PVC Type II

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
3115	For 1-1/2 in. PVC Pipe, 3/4 in. SX 1 in. Spigot	3220	For 2 in. PVC Pipe, 1-1/2 in. Socket or 2 in. Spigot
3120	For 2 in. PVC Pipe, 3/4 in. Socket or 1 in. Spigot	3225	For 2-1/2 in. PVC Pipe, 1-1/2 in. Socket or 2 in. Spigot
3125	For 2-1/2 in. PVC Pipe, 3/4 in. Socket or 1 in. Spigot	3230	For 3 in. PVC Pipe, 1-1/2 in. Socket or 2 in. Spigot
3130	For 3 in. PVC Pipe, 3/4 in. Socket or 1 in. Spigot	3240	For 4 in. PVC Pipe, 1-1/2 in. Socket or 2 in. Spigot
3140	For 4 in. PVC Pipe, 3/4 in. Socket or 1 in. Spigot	3260	For 6 in. PVC Pipe, 1-1/2 in. Socket or 2 in. Spigot
3160	For 6 in. PVC Pipe, 3/4 in. Socket or 1 in. Spigot	3280	For 8 in. PVC Pipe, 1-1/2 in. Socket or 2 in. Spigot

## Clamp-It™ Rigid PVC Saddle for PVC Pipe

Pipe Pressure Rated @ 200 PSI @ 72°F | NSF/ANSI 61 +372 | PVC Type II

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
421507	For 1-1/2 in. PVC Pipe, 3/4 in. FPT	444020	For 4 in. PVC Pipe, 2 in. FPT
421510	For 1-1/2 in. PVC Pipe, 1 in. FPT	446007	For 6 in. PVC Pipe, 3/4 in. FPT
422007	For 2 in. PVC Pipe, 3/4 in. FPT	446010	For 6 in. PVC Pipe, 1 in. FPT
422010	For 2 in. PVC Pipe, 1 in. FPT	446012	For 6 in. PVC Pipe, 1-1/4 in. FPT
422012	For 2 in. PVC Pipe, 1-1/4 in. FPT	446015	For 6 in. PVC Pipe, 1-1/2 in. FPT
422015	For 2 in. PVC Pipe, 1-1/2 in. FPT	446020	For 6 in. PVC Pipe, 2 in. FPT
432007	For 2 in. PVC Pipe, 3/4 in. Slip	448010	For 8 in. PVC Pipe, 1 in. FPT
432010	For 2 in. PVC Pipe, 1 in. Slip	448015	For 8 in. PVC Pipe, 1-1/2 in. FPT
432012	For 2 in. PVC Pipe, 1-1/4 in. Slip	448020	For 8 in. PVC Pipe, 2 in. FPT
432015	For 2 in. PVC Pipe, 1-1/2 in. Slip	453007	For 3 in. PVC Pipe, 3/4 in. Slip
432510	For 2-1/2 in. PVC Pipe, 1 in. Slip	453010	For 3 in. PVC Pipe, 1 in. Slip
432515	For 2-1/2 in. PVC Pipe, 1-1/2 in. Slip	453015	For 3 in. PVC Pipe, 1-1/2 in. Slip
432520	For 2-1/2 in. PVC Pipe, 2 in. Slip	453020	For 3 in. PVC Pipe, 2 in. Slip
443007	For 3 in. PVC Pipe, 3/4 in. FPT	454010	For 4 in. PVC Pipe, 1 in. Slip
443010	For 3 in. PVC Pipe, 1 in. FPT	454015	For 4 in. PVC Pipe, 1-1/2 in. Slip
443012	For 3 in. PVC Pipe, 1-1/4 in. FPT	454020	For 4 in. PVC Pipe, 2 in. Slip
443015	For 3 in. PVC Pipe, 1-1/2 in. FPT	456010	For 6 in. PVC Pipe, 1 in. Slip
443020	For 3 in. PVC Pipe, 2 in. FPT	456015	For 6 in. PVC Pipe, 1-1/2 in. Slip
444007	For 4 in. PVC Pipe, 3/4 in. FPT	456020	For 6 in. PVC Pipe, 2 in. Slip
444010	For 4 in. PVC Pipe, 1 in. FPT	458015	For 8 in. PVC Pipe, 1-1/2 in. Slip
444012	For 4 in. PVC Pipe, 1-1/4 in. FPT	458020	For 8 in. PVC Pipe, 2 in. Slip
444015	For 4 in. PVC Pipe, 1-1/2 in. FPT		

## Clamp-It™ Rigid PVC Saddle for Poly Pipe

Pipe Pressure Rated @ 125 PSI @ 72°F | NSF/ANSI 61 +372 | PVC Type II

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
322010P	For 2 in. Poly Pipe, 1 in. FPT	332010P	For 2 in. Poly Pipe, 1 in. Slip
331510P	For 1-1/2 in. Poly Pipe, 1 in. Slip	344007P	For 4 in. Poly Pipe, 3/4 in. FPT